

# 4BC8

## Medium-Mu Twin Triode

With Semiremote-Cutoff Characteristic

### 9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4BC8 is the same as the 6BC8 except for the following items:

Heater Characteristics and Ratings (*Design-Center Values*):

Current . . . . .	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600 . . . . .	4.2	volts
Warm-up time (Average) . . . . .	11	sec

# 4BL8

## Medium-Mu Triode— Sharp-Cutoff Pentode

### 9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4BL8 is the same as the 6BL8 except for the following items:

Heater Characteristics and Ratings (*Design-Center Values*):

Current . . . . .	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600 . . . . .	4.6	volts

# 4BN6

## Beam Tube

### 7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4BN6 is the same as the 6BN6 except for the following items:

Heater Characteristics and Ratings (*Design-Maximum Values*):

Current . . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450 . . . . .	4.2	volts
Warm-up time (Average) . . . . .	11	sec

